

## Type C/CO/CR Dynamic 1½ Hour Sizing Chart

'C' = Duct Connection Diameter/Height

'H' = Overall Damper Height

Type C/CO/CR maximum single section duct connection collar diameter/height is 20" (508) vertical or horizontal mount. Larger collar diameters/heights up to 44" (1118), vertical mount only, will be made in 2 sections high. Larger heights up to 68" (1727), will be manufactured in 3 sections high. Dynamic horizontal mount multiple section assemblies are not available (contact factory).

Damper overall width  
= duct diameter/width + 2" (51).

C	H
4 (102)	6 (152)
5 (127)	7 (178)
6 (152)	8 (203)
7 (178)	9 (229)
8 (203)	11 (279)
9 (229)	12 (305)
10 (254)	13 (330)
11 (279)	14 (356)
12 (305)	15 (381)
13 (330)	16 (406)
14 (356)	17 (432)
15 (381)	18 (457)
16 (406)	20 (508)
17 (432)	21 (533)
18 (457)	22 (559)
19 (483)	23 (584)
20 (508)	24 (610)
21 (533)	24 (610)
22 (559)	25 (635)
23 (584)	26 (660)
24 (610)	27 (686)
25 (635)	28 (711)
26 (660)	29 (737)
27 (686)	30 (762)
28 (711)	31 (787)
29 (737)	32 (813)
30 (762)	33 (838)
31 (787)	34 (864)
32 (813)	35 (889)
33 (838)	36 (914)
34 (864)	37 (940)
35 (889)	38 (965)
36 (914)	39 (991)
37 (940)	41 (1041)
38 (965)	42 (1067)
39 (991)	43 (1092)
40 (1016)	44 (1118)
41 (1041)	45 (1143)
42 (1067)	46 (1168)
43 (1092)	47 (1194)
44 (1118)	48 (1219)
45 (1143)	48 (1219)
46 (1168)	49 (1245)
47 (1194)	50 (1270)
48 (1219)	51 (1296)
49 (1245)	52 (1321)
50 (1270)	53 (1346)
51 (1296)	54 (1372)
52 (1321)	55 (1397)

**DIMENSIONS IN INCHES (MM)**

DIMENSIONS IN INCHES (MM)